

**U**  
RANGE



# Ultra Low Freezers

B Medical Systems | U Range

Ultra Low Freezers are devices intended for the storage of blood components and blood plasma, human cells, tissues and other laboratory samples at ultra low temperatures down to  $-86^{\circ}\text{C}$ .

**Compliant to DIN 58375 | Medical Device Class IIa according to MDD 93/42/EEC**

**4**  
MODELS

**-82°C**  
TEMPERATURE

**300 > 600**  
PLASMA BAGS  
(350ml)

**SN**  
CLIMATE  
CLASS



medical  
systems

**SAVING LIVES**  
THROUGH RELIABLE  
AND INNOVATIVE  
TECHNOLOGY

**Blood Management Solutions**



# Safety Standards

## B Medical Systems



The Safety Standards developed by B Medical Systems define certain significant technical features of a product. These ensure the safe storage of the preparations as well as setting the highest standards of safety for the user.

PREMIUM LINE	
<input checked="" type="radio"/>	B Medical Systems Electronics
<input checked="" type="radio"/>	B Medical Systems 7" full touchscreen display
<input checked="" type="radio"/>	Power indicator light and digital temperature indicator (display: 0.1 digits)
<input checked="" type="radio"/>	Controlled fan cooling system for constant temperature and even temperature distribution across the entire refrigerating chamber
<input checked="" type="radio"/>	Automatic switch-off of the evaporator fans when the door opens
<input checked="" type="radio"/>	Self-contained alarm system with integrated battery takes over the alarm function and temperature value measurements in case of system failure for at least 48 hours
<input checked="" type="radio"/>	Acoustic and visual alarm signal in case of temperature alarm and system failure
<input checked="" type="radio"/>	The alarm history function on the electronic stores all the relevant values during a temperature alarm, such as: min., max., average temperature and alarm duration
<input checked="" type="radio"/>	Remote transmission alarm signal (via potential-free contact) in case of temperature alarm (change-over contact)
<input checked="" type="radio"/>	Door opening alarm (visual / acoustic)
<input checked="" type="radio"/>	Designed and tested for climatic class SN (ambient temperature range +10°C to +32°C)
<input checked="" type="radio"/>	Interior made from stainless steel
<input checked="" type="radio"/>	Additional remote transmission alarm signal (via potential-free contact) in case of system failure (change-over contact)
<input checked="" type="radio"/>	Smooth castors for optimum flexibility of movement
<input type="radio"/>	External water cooling
<input type="radio"/>	Ambient temperature sensor
<input checked="" type="radio"/>	*B Connected - Universal software for the monitoring of refrigeration devices, including the acquisition, recording and visualization of temperature data
<input checked="" type="radio"/>	Ethernet interface for the visualization of all operating and control functions (hardware and software settings) via *B Connected monitoring software on a peripheral device (computer)

# Ultra Low Freezers

## B Medical Systems | U Range

4 models • Volume 451 > 895 L • Set temperature  $-82^{\circ}\text{C}$  • Climate class SN • Compliant to DIN 58375 | MDD 93/42/EEC, Class IIa

In conformity with national and international guidelines, regulations for Medical Devices offering reliability, efficiency and safety at an optimal price.

MODELS U401-501-701-901 | PREMIUM LINE




### Exclusive integrated electronics handle bar (Patent pending)

All functionalities are easily accessible:

- Digital control with full functionalities - New B Medical Systems 7" full touchscreen display integrated at optimal level in the door handle with pre-installed connection allowing exclusive °B Connected monitoring functionalities
- Open/close - Heavy duty door lock mechanism

### High quality materials

New high quality coating, certified medical devices quality and antibacterial, high quality steel for better longevity and easy hygiene control.



### Special features

- Integrated pressure release valve in the door permitting faster opening in one move, and offering easy access for cleaning
- Insulated inner doors for significantly lower loss of cooling when open
- Full compatibility of inner modules and rails, no need to buy new racks, you can keep racks previously used in different models

### Versatile modularity

Excellent storage capacity and modularity - Large choice of racks offering modularity for every need.



**Ultra Low Freezers are devices intended for the storage of blood components and blood plasma, human cells, tissues and other laboratory samples at ultra low temperatures down to  $-86^{\circ}\text{C}$ .** U models reflect the highest and most uncompromising requirements with state-of-the-art technology and economy. The cooling system is optimally designed with respect to energy consumption as well as to the development of waste heat and noise. Standard factory setpoint is  $-82^{\circ}\text{C}$ , temperature is adjustable from  $-40^{\circ}\text{C}$  to  $-86^{\circ}\text{C}$ .



## Technical Data

### General features



**U401**

**U501**

**U701**

**U901**

<i>Gross / Net volume (l)</i>	451 / 434	598 / 577	747 / 720	895 / 863	
<i>Storage capacity</i>	<i>Plasma bags</i>	300 (350ml)	400 (350ml)	500 (350ml)	600 (350ml)
	<i>Cryoboxes</i>	300 (model H50)	400 (model H50)	500 (model H50)	600 (model H50)
	<i>Vials</i>	30000 (2ml)	40000 (2ml)	50000 (2ml)	60000 (2ml)
<i>Set temperature (preset)</i>	-82°C				
<i>Set temperature (setting range)</i> <i>can be adjusted in steps of 0.1°C</i>	-86°C to -40°C				
<i>Temperature cold / warm alarm limit</i>	-87°C / -77°C				
<i>Hold over time (-80°C to -60°C)</i>	1 h 18 min.	1 h 18 min.	1 h 18 min.	1 h 24 min.	
<i>Climate class (ambient temperature range)</i>	SN (+10°C to +32°C)				
<i>Defrosting technique</i>	Manual				
<i>Refrigerant type</i>	R290 / R170				
<i>External dimensions H x W x D (mm)</i>	1988 x 699 x 1039	1988 x 845 x 1039	1988 x 992 x 1039	1988 x 1139 x 1039	
<i>Inner dimensions H x W x D (mm)</i>	1370 x 447 x 713	1370 x 590 x 713	1370 x 740 x 713	1370 x 887 x 713	
<i>Net weight with standard equipment (kg)</i>	250	276	297	320	
<b>Energy Saver</b>	<i>Supply voltage (V)</i>	230	230	230	230
	<i>Frequency (Hz)</i>	50	50	50	50
	<i>Power (W)</i>	2000	2000	2000	2000
	<i>Energy consumption (kWh/24h)</i>	9.1	11.3	11.9	12.4
	<i>Heat emission (Kcal/h)</i>	326	404	426	444
	<i>Compressor running time (%)</i>	46	51	50	59
	<i>Noise level (dB(A))</i> <i>(at 1m height &amp; 1m distance)</i>	60	62	63	62

### EXAMPLE OF "STABLE RUNNING (TEMPERATURE STABILITY)"

For all models, temperature distribution graphs for the stages "Cool Down (Cooling)", "Stable Running (temperature stability)" and "Hold Over (temperature graphs, for example in case of system failure)" are available upon inquiry for various voltages. Determined at 5 measuring points per level or compartment (empty).

#### U401

Voltage: 230V / 50Hz


Ambient temperature: +25°C

Relative humidity: 45%

Set point: -82°C

Cold alarm: -87°C

Warm alarm: -77°C





## Technical Data Specifications



**U401**



**U501**



**U701**




**U901**

<b>Regulation sensor</b> <i>Precision (from -80°C to +180°C) ± 0.2°C</i>	PT1000	
<b>Display sensor</b> <i>Precision (from -80°C to +180°C) ± 0.2°C in reference body / 100 ml DOW corning 200-5CST (Silicon Oil)</i>	PT1000	
<b>Accu data / function time of the control panel when system failure</b>	12 V - 7 AH / 48h	
<b>Relative humidity at +32°C</b>	≤ 75%	
<b>Door insulation (polyurethane)</b>	65-82 mm PU with 20 mm VIP	
<b>Casing insulation (polyurethane)</b>	77-82 mm PU with 20-30 mm VIP	
<b>Material</b>	<i>Inner body</i>	Stainless steel (1.4301)
	<i>Outer body</i>	DX51D + Z100 coated
	<i>Inner door</i>	Stainless steel (1.4301)
	<i>Outer door</i>	DX51D + Z100 coated
	<i>Separate interior doors</i>	Anodized aluminium
<i>Shelf</i>	Stainless steel (1.4301)	
<b>European Medical Device Directive</b>	93 / 42 / EEC, Class IIa (models: 230 V - 50 Hz)	
<b>EMC directive</b>	2014 / 30 / EU (models: 230 V - 50 Hz)	
<b>Low voltage directive</b>	2014 / 35 / EU (models: 230 V - 50 Hz)	
<b>FDA regulation</b>	Class II medical devices acc. to 21CFR Part 864.9700 (models: 220 V - 60 Hz)	
<b>cCSAus certificate</b>	Yes (models: 220 V - 60 Hz)	
<b>GMP - Clean room classification</b>	Class ISO 5 / EC GMP A	

Subject to change without prior notice. Some of the accessories shown in the pictures are optional.

**SAVING LIVES THROUGH RELIABLE AND INNOVATIVE TECHNOLOGY**



ST-SHELF  
(STAINLESS STEEL)




SEPARATE  
INTERIOR  
DOORS



ICE  
SCRAPER

## Equipment Standard & optional

	U401	U501	U701	U901
<i>B Medical Systems Electronics 7" full touchscreen display</i>	●	●	●	●
<i>Interior equipment</i> <i>ST-Shelf</i>	● 3	● 3	● 3	● 3
<i>Separate interior doors in order to minimize the loss of cold air</i>	●	●	●	●
<i>Integrated pressure release valve</i>	●	●	●	●
<i>°B Connected - Monitoring Software</i>	●	●	●	●
<i>Ethernet interface</i>	●	●	●	●
<i>Ambient temperature sensor</i>	○	○	○	○
<i>Potential-free alarm contact in case of system failure</i>	●	●	●	●
<i>Integrated port for external sensor (installed by customer)</i>	●	●	●	●
<i>External water cooling</i>	○	○	○	○
<i>CO<sub>2</sub> BackUp / Emergency cooling system</i>	○	○	○	○
<i>Ice scraper</i>	●	●	●	●
<i>Smooth castors with stabilizers</i>	●	●	●	●
<i>Door hinge Right   Left</i>	●   ○	●   ○	●   ○	●   ○



### INTEGRATED PRESSURE RELEASE VALVE

This aluminium die cast handle offers a strong and ergonomic feeling that allows the user to open the door with one hand. Inside the freezers, the vacuum will be automatically removed through a release valve, located in the door, in order to allow easy cleaning.

The handle is equipped with an electric lock that can be deactivated through the user interface.

● Standard ○ Optional - Not available

Subject to change without prior notice.




**CRYO-RACK**  
Available for  
Cryoboxes  
H50 / H75 / H100



**D-RACK**  
Available for  
Cryoboxes  
H50 / H75 / H100



**D-RACK  
MICROTITER**



**CARTON  
CRYOBOX**  
(Shown with  
carton separator)


## Accessories Optional

	U401	U501	U701	U901
<i>Cryo-Rack H50 / H75 / H100 for the storage of Cryoboxes</i>	○ ≤ 12	○ ≤ 16	○ ≤ 20	○ ≤ 24
<i>D-Rack H50 / H75 / H100 for the storage of Cryoboxes</i>	○ ≤ 12	○ ≤ 16	○ ≤ 20	○ ≤ 24
<i>D-Rack microtiter H22</i>	○ ≤ 12	○ ≤ 16	○ ≤ 20	○ ≤ 24
<i>Carton Cryobox</i>	<i>H50 (H 50 x W 136 x D 136 mm)</i>	○ ≤ 300 (with Cryo-Rack)	○ ≤ 400 (with Cryo-Rack)	○ ≤ 600 (with Cryo-Rack)
	<i>H75 (H 75 x W 136 x D 136 mm)</i>	○ ≤ 240 (with D-Rack)	○ ≤ 320 (with D-Rack)	○ ≤ 480 (with D-Rack)
	<i>H100 (H 100 x W 136 x D 136 mm)</i>	○ ≤ 180	○ ≤ 240	○ ≤ 300
<i>Carton separator for Cryoboxes H50 / H75 / H100</i>	○ ≤ 120	○ ≤ 160	○ ≤ 200	○ ≤ 240
<i>S-Rack (H 100 x W 113 x D 638 mm) for the storage of bags</i>	○	○	○	○
<i>Separator for S-Rack to facilitate the handling and storage management of bags</i>	○ ≤ 12	○ ≤ 16	○ ≤ 20	○ ≤ 24
<i>Temperature chart recorder pre mounted (in the form of a circular chart recorder)</i>	○ ≤ 12	○ ≤ 16	○ ≤ 20	○ ≤ 24




### VERSATILE MODULARITY


Excellent storage capacity and modularity -  
Large choice of racks offering modularity -  
for every need.



**S-RACK**



**SEPARATOR  
FOR S-RACK**



**TEMPERATURE  
CHART  
RECORDER**  
(sample image)

# Full functionalities at a glance

## B Medical Systems | Electronics

### The new B Medical Systems Electronics

offers a wide range of adjustment and diagnostic facilities as well as additional protection / warning operations (via external alarm operations, histories and individual display signals).

**PREMIUM LINE** | Multi-function electronics with 7" full touchscreen display, integrated at optimal level in the door handle with pre-installed connection allowing exclusive °B Connected monitoring functionalities.



#### Power switch OFF / ON

- To switch on press the ON/OFF button for 1 second. The green LED will light up
- Switch off protected by password. The door will automatically unlock before powering down



#### Touchscreen 7" full display

During normal operation the display shows:

- At the top: current voltage, current time, gasket heater and login status (user level)
- Left-hand side: temperature of the regulation sensor (displaying this temperature can be disabled through the settings) and internal temperature displayed in °C (Celsius) or °F (Fahrenheit) in increments of 0.1°
- Right-hand side: touch buttons to access door unlock, clean, menu, alarm mute and message functions



#### USB-port & SD-card-slot

#### Acoustic and visual alarm signal

When an alarm occurs, the red alarm LED lights up and an acoustic signal sounds. The corresponding alarm message appears on the display together with the measured inside temperature. If several alarms occur simultaneously, the messages will be shown alternately.



#### Keycard reader

Login / Unlock using a NFC card

#### Touch buttons

- DOOR UNLOCK button: unlocks the door of the device
- CLEAN button: the cleaning button allows the user to disable the touch capability of the screen for a short period of time in order to clean the screen. This button is replaced by the logout button when any user is logged in
- MENU button: allows access to the menu screen
- ALARM MUTE button: deactivates the acoustic alarm for a predefined period of time
- MESSAGE button: during a warning or alarm situation, the color of this button and the corresponding level will change. Information on an active alarm and warning is accessible by pressing the message button



# Optimum control and protection

## B Medical Systems | °B Connected

### °B CONNECTED | MONITORING SOFTWARE

*Universal software for the monitoring of refrigeration devices, including the acquisition, recording and visualization of temperature data.*



- Unique monitoring software for the full range of Blood Management Solutions and Medical Refrigeration products
- Web-based interfaces for computers and mobile devices
- Modern design for simple and intuitive use
- Graphic display of temperature curves
- Integrated event and activity history of appliances' components
- Data recording on centralized database for long-term archiving
- Easy setting of specific alarm forwarding, via email or SMS
- Generation of reports compiling crucial data and activities
- Temperature and detailed device data export for third-party software
- Important price advantage compared to a traditional circular chart recorder and its spare parts
- REST API to access raw data directly from the database in read only mode

#### KEY BENEFITS:

- Unique interface for the monitoring of the full range of refrigeration devices
- Centralized database providing data access to entire customer network

#### 1 CONFIGURATION




##### USER MANAGEMENT

- Password login
- Access right



##### DEVICE SETTINGS

- Device information
- Device & user configuration



##### ALARM PROFILE

- Parameters of the alarm profile (day, hour, minute)
- Alarm management

#### 2 DISPLAYING




##### DETAILED DISPLAY

- Optimised design for mobile and touch compatible devices
- Support of multiple languages
  - Real time data: Current temperatures, set point, upper and lower limit, door state, compressor runtime
- Log data: Events, alarms within date/time, event type, description of the event. Event and alarm confirmation function
- Batch management: Read in of plasma bags with a barcode scanner
  - Movement state and door control of Agitator devices
  - Parameter settings of each device: Factory settings, real time clock, language, firmware version, RS485 address, IP address


°B Connected offer a highly flexible system that is adaptable to specific customer requirements

- > Complete & legally safe documentation of temperature data
- > Comprehensive applications and diagnostic possibilities



#### REAL TIME GRAPHICS

- Graphic temperature progress (in real time)
- Adjustable time axis
- Offline navigation



#### CONTROL CENTER


- Overview (Control Monitor) of all monitored appliances:
- Information regarding status, appliance name, location, connection, upper and lower limit, current temperature, events / alarms
  - Dashboard to combine several temperature measurements in one single graph

### 3 ANALYSING



#### INTERACTIVE ANALYSIS

- No limitation in terms of time range
- Freely scalable
- Detailed information for any point of time
- Temperature data, events and alarms
- Login history and audit trails



#### PRINTED ANALYSIS

- Customisable print reports on daily, weekly and monthly basis
- Exports in various file types
- Standardised format



## Blood Management Solutions

Safe global blood management: from collection to transfusion, transportation, processing and storage



## Vaccine Cold Chain

Reliable solutions for safe vaccination around the world



## Medical Refrigeration

State-of-the-art technology for the exacting needs of the medical world



### After Sales support and service

We strive to provide you with the highest standards of service; not only through our selected distributors and partners for all your maintenance and service but also our second line trouble shooting and after sales service. This Factory based group of engineers is there to help our partners and yourself to get the best solution for your cold storage needs.

### Our Global Expertise



### SAVING LIVES THROUGH RELIABLE AND INNOVATIVE TECHNOLOGY

B Medical Systems (formerly Dometic Medical Systems) has more than 35 years' experience in the medical refrigeration sector.

The company, formerly known as Electrolux Medical Systems, was founded in 1979 when the World Health Organization approached Electrolux in Vianden, Luxembourg, to create a solution for the safe storage and transport of vaccines around the world. In 2001, Electrolux Medical Systems became part of the Dometic Group, and was renamed Dometic Medical Systems. Having established a legitimate reputation in the medical equipment industry, the company has also become a global leader in vaccine cold chain.

#### B Medical Systems S.à r.l.

17, op der Hei  
L - 9809 Hosingen, Luxembourg

Tel.: (+352) 92 07 31-1  
Fax: (+352) 92 07 31-300  
info@bmedicalsistemas.com



[www.bmedicalsistemas.com](http://www.bmedicalsistemas.com)



### Luxembourg, in the heart of Europe

